

PLCスプリッター—LGXボックス & ラックマウント PLC Splitter LGX Box & Rack Mount

Optical Specifications

Parameter	Unit	Specification (P Grade)											
		1X2	1X3	1X4	1X6	1X8	1X12	1X16	1X24	1X32	1X64	1X128	
Operation Wavelength	nm	1260~1650											
Insertion Loss (Max.)	dB	4.3	6.2	7.4	9.8	10.7	12.5	13.9	16.5	17.2	21.5	25.5	
Uniformity (Max.)	dB	0.5	0.6	0.8	0.8	1.0	1.0	1.4	1.5	1.6	2.0	2.6	
Polarization Dependent Loss	dB	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.8	
Return Loss	dB	≥50											
Directivity	dB	≥50											

Parameter	Unit	Specification (P Grade)							
		2X2	2X4	2X8	2X16	2X32	2X64	2X128	
Operation Wavelength	nm	1260~1650							
Insertion Loss (Max.)	dB	4.3	7.6	11.0	14.8	17.9	21.5	25.8	
Uniformity (Max.)	dB	0.8	1.0	1.2	1.5	1.8	2.0	3.0	
Polarization Dependent Loss	dB	0.2	0.3	0.3	0.3	0.3	0.5	1.0	
Return Loss	dB	≥50							
Directivity	dB	≥50							

Note: All the data above does not include connectors.

UPC Connectors: IL add 0.2 dB, APC Connectors: IL add 0.3 dB.

Environmental Conditions

Operating Temperature	°C	-40~+85
Storage Temperature	°C	-40~+85
Operating Humidity	%RH	≤93
Storage Humidity	%RH	≤93



Order Information

PLC	Port	Fiber Type	Package	Input	Output	Pigtail	Connector
-	-	-	-	-	-	-	-

Port	0101=1x1, 0102=1x2, ..., 0404=4x4, ..., 0132=1x32, 0232=2x32
Fiber Type	1=G652D, 2=G657A
Package Dimension	D, E, ..., F, K, U, X
Input Fiber Type	L=900μm Loose tube, S=2.0mm, R=3.0mm, 0=Adapter
Output Fiber Type	L=900μm Loose tube, S=2.0mm, R=3.0mm,, 0=Adapter
Pigtail Length	05--20=0.5--2.0m, 0=Adapter, X=Others
Connector Type	FU=FC/UPC, FA=FC/APC, SU=SC/UPC, SA=SC/APC, ST=ST/UPC, LU=LC/UPC, LA=LC/APC, 00=None, X=Others

Packaging Information

Items	1x2	2x2	1x3	1x4	2x4	1x6	1x8(127)	1x8(250)	2x8
19" Rack Mount	XU								
Items	1x12	1x16	2x16	1x24	1x32	2x32	1x64	2x64	
Rack Mount	XU/XG								

Package Dimensions (mm)

XU	1,2,3,4U 19" Rack Mount	XG	1,2,3,4U LGX
X	Custom Specifies		

* 特殊仕様の対応も可能です。詳細は、お手数ですがお問い合わせフォームにお願いします。

Contact your OSTenp representative for information on specifications and availability.

Website: www.ostenp.com

E-mail: sales@ostenp.com

Tel.: 046-296-1750 Fax.: 046-296-1755